

# VITA CABLES — Veehi Engineering Private Limited

Your Power, Our Cables & Wires | BIS Certified · NABL Tested · IS 694 / IS 1554 Compliant

PRICE LIST | Valid From: 01/05/2026 To: 31/07/2026 (All prices in ₹ per metre, exclusive of GST)

## 3 CORE FLAT SUBMERSIBLE CABLE — PVC INSULATED | IS 694 | Suitable for Submersible Pump Motors

Size (sq mm)	Configuration (Cores × Strands/Dia)	Conductor Resistance (Ω/km)	Insulation Thickness (mm)	Flat Width (approx. mm)	Overall Thickness (approx. mm)	Approx. Wt (kg/km)	MRP (₹/mtr)
1.5 sq mm	3C × 22/0.30	12.10	0.7	13.0	5.5	70	133
2.5 sq mm	3C × 36/0.30	7.41	0.8	15.5	6.2	105	215
4.0 sq mm	3C × 56/0.30	4.61	0.8	18.5	7.0	150	320
6.0 sq mm	3C × 84/0.30	3.08	0.8	22.0	7.8	210	472
10.0 sq mm	3C × 80/0.40	1.83	1.0	28.0	9.5	335	657
16.0 sq mm	3C × 126/0.40	1.15	1.0	34.0	11.0	510	780
25.0 sq mm	3C × 196/0.40	0.727	1.2	42.0	13.5	760	1274
35.0 sq mm	3C × 490/0.30	0.554	1.2	44	14.5	820	2996
50.0 sq mm	3C × 700/0.30	0.386	1.4	58	19	970	4690

★ Flat cable design — ideal for borewell & submersible pump motor wiring. PVC outer jacket resists moisture & oil.

★ Available in standard black jacket. Coil sizes: 30m, 50m, 100m. Minimum order: 50 mtrs.

★ Prices per metre excluding GST @18%. Rates linked to copper LME — confirm at time of order.

For orders & enquiries contact: VITA Cables — Veehi Engineering Private Limited |  
Phone: +91 9898097945 | Email: sales@vitacable.com | Website: www.vitacable.com

